



Pros and Cons of Sand on Ice and Snowpack



This picture was taken in March after a season of spreading sand on a hill. Sand remains on the road and roadsides. A catch basin at the bottom of the hill empties into a wetland.

deposits on roadways. Environmental concerns dictate that sand be swept up each spring. Sweeping sand also picks up other debris and various compounds. Agencies must dispose of the material as a solid waste.

Sweeping picks up only a small percent of the total sand applied during a typical winter. The rest remains in the environment, much of it in catch basins or on or around roadways. Sand retained in catch basins should be periodically removed. This material, too, must be disposed of as solid waste. (A pending New Hampshire Department of Environmental Services fact sheet will address disposal of street sweepings and catch basin materials.)

Many highway departments apply sand on snow and ice covered roads to increase friction and improve road safety. Yet, significant friction increases occur in only a few situations. This article will describe those situations and the affects of sand on the environment.

Environmental Concerns

Agencies tend to spread sand many times throughout the winter months. Sand is expensive. It also can create large debris

Much of the sand not retained in catch basins stays in drainage pipes, decreasing their capacity. The rest is carried to outfalls, becoming sediment in ditches and water bodies.

Some of the sand on roadsides ends up in the ground, diminishing soil quality. Much of it becomes sediment, in many instances carried into streams, rivers, ponds, or lakes.

Study Results

Studies show that the effects of sanding are temporary, whether spread dry or prewetted. Abrasives do little to improve driving conditions on roads with high traffic volume. When dry sand is spread, 30% of it immediately scatters. Over time, cars usually displace most of the remaining sand. As few as 8 to 12 vehicles can sweep it from snow covered highway surfaces. Even with light traffic, friction gained from dry sand is quickly diminished.

University of Iowa (UI) researchers have drawn conclusions about methods to prewet abrasives with a chemical deicing brine. One method is to prewet abrasives in the stockpile to prevent their freezing. Such prewetting has little effect on the ability of the abrasives to remain on the pavement surface when delivered.

Some agencies prewet abrasives while loading trucks. Researchers found no evidence that such prewetting increases abrasives staying on the road surface.

The final prewetting method is to add about 10 gallons of sodium chloride or calcium chloride brine per ton of abrasives at the truck spinner or tailgate. Studies indicate that prewetting salt and other solid chemicals helps to keep them on the road surface when first delivered. It is less clear that prewetting helps it to stay there. The researchers drew the same conclusions for sand.

In summary, none of the prewetting methods appears to help sand stay on roads.

Recommended Practices

The UI study examined abrasive use on Iowa county roads. The researcher concluded that sand has varying levels of effectiveness on different classes of roads. He recommended the following changes in practice, which are summarized in Table I.

- **High Speed Urban Roads.** For urban streets with posted speed limits above 30 mph, there is no significant value in placing abrasives. Research recommends plowing and applying chemicals to achieve bare pavement.
- **Low Speed Urban Roads.** For urban streets with posted speed limits less than 30 mph, there is less abrasive dispersion. Abrasives should be limited to parts of the road where motorists must brake, accelerate, or maneuver. Even then, abrasives should be applied only when it will likely take a long time to provide bare pavement.
- **Urban Intersections.** Urban intersections are relatively low-speed traffic locations. Abrasives could be placed if needed. However, they should be used only when an intersection might be snow or ice-covered beyond a normal period.
- **Rural Roads.** Both paved and gravel roads can expect to see high-speed traffic. Abrasives will not stay on the road for any reasonable amount of time. Abrasives should be applied on hills and curves only on low-speed low-volume roads. Paved rural roads should be plowed

and chemical applied to achieve bare pavement. The recommended gravel rural roads approach should be simply to groom the snow pack.

- **Rural Intersections.** Again, gravel versus paved roads must be considered. An intersection should be considered “paved” only if all intersecting roads are paved. Road segments where motorists must stop or yield are low-speed traffic locations. Abrasives could be placed if needed. The preferred approach for paved roads is to plow and apply chemicals to achieve bare pavement. On gravel parts of intersections, abrasives may be applied over that part of the road where speeds less than 30 mph are expected.

Table 1 Recommended Abrasives Applications	
Road Type	Use of Dry Abrasives
High Speed Urban Roads	Inappropriate
Low Speed Urban Roads	Only in certain locations, and when snow pack will persist
Urban Intersections	Only when snow pack will persist
Rural Roads, Paved	Inappropriate
Rural Roads, Gravel	Only on low speed sections (perhaps hills and curves)
Rural Intersections	Only on low speed approach length of gravel roads

Sand remaining on gravel roads after spring thaw is a poor wearing course

material. Some New Hampshire road managers report significant friction increases from spreading crushed aggregate on gravel hills and curves. Several have successfully used 5/8-inch minus aggregate. In addition to safer roads in the winter, these are better wearing course materials after the spring thaw. Following the UI recommendations above, managers should consider such material at gravel road intersections.

Sand-salt mixtures help keep the sand from freezing. A 10:1 mixture, 10 parts sand to one part salt, is usually more than sufficient to prevent freezing.

Mixtures with sufficient salt will melt ice and snowpack. Sand melts no snow or ice. The amount of melting depends on the amount of salt applied per unit area. For example, studies have shown that agencies should apply at least 300 pounds per road mile to melt ice or hard snow pack at temperatures just below freezing. For a 1:1 or 50%-50% mix, the agency must spread 300 pounds of salt per mile of sand to apply the necessary salt. Sand to salt mixes of 2:1 require 600 pounds per mile of sand to spread enough salt. Higher ratios require even more sand.

As established above, sand is useful only in certain situations, and often adversely affects the environment. It is expensive to spread, pick up, and dispose of. With only a few exceptions, the best winter operations practice to provide safe roads is to plow and

apply chemicals to achieve bare pavement. For gravel road hills, curves, and intersections, spreading crushed aggregate appears to be a good alternative to sand.

Beth Terney, UNH T² Center Project Assistant, contributed to this article.

Sources:

“Dry Sand on Winter Roads Provides Little Benefit.” *Technology News*, Jan-Feb 2001, 4-5.

“Saving Money and the Environment.” Federal Highway Administration. June 2001. <http://www.fhwa.dot.gov////////winter/roadsvr/CS092.htm>.

Nixon, Wilfrid A. “The Use of Abrasives in Winter Maintenance: Final Report of Project TR 424.” March 2001.
<http://www.sicop.net/Abrasives%20report.pdf>, June 2001.